## **EON710**

### 10-inch Powered PA Speaker with Bluetooth




#### **SPEC SHEET**



#### **OVERVIEW**

The JBL EON710 10-inch loudspeaker, part of JBL's new EON700 Series of powered PAs, brings brings advanced DSP and control to portable systems for live sound and installed applications, with class-leading volume and clarity and comprehensive features that make setup and operation a breeze.



**REAR PANEL CONNECTIONS** 

#### **PRODUCT HIGHLIGHTS** ■

- Custom-designed 10-inch woofer
- 2414H compression driver
- Redesigned high-frequency horn
- Power: 1,300W Peak / 650W RMS
- Frequency response: 52Hz 20kHz (-10) 65Hz - 20kHz (-3)
- Max SPL: 125 dB
- Dispersion: 110° H x 60° V
- Audio I/Os: 2 XLR Combo, 1 XLR passthrough
- Advanced dbx DSP: Automatic Feedback Suppression, ducking, 100ms speaker delay, parametric EQ

- Built-in 3-channel digital mixer
- Color backlit LCD screen provides easy access to functions
- Universal JBL Pro Connect app control
- Bluetooth 5.0 streaming and control
- Durable polypropylene cabinet and metal grille
- Ergonomic handle simplifies transport
- Built-in pole mount and optional EON700 Universal Yoke Mount expand system configuration options
- Stackable cabinets for easy storage
- Net Weight: 12.0 kg (26.46 lbs.)
- Shipping Weight: 15.4 kg (33.95 lbs.)

# **EON710**

## 10-inch Powered PA Speaker with Bluetooth



### **SPEC SHEET**

### **SPECIFICATIONS** ■

Custom Tune	10IN Developed Levidopoolica
System Type	10IN Powered Loudspeaker
Woofer Model	710G
Woofer Size	10"
Woofer Magnet	Ferrite
<b>Woofer Voice Coil</b>	2"
Tweeter Model	2414H Compression Driver
Tweeter Size	1"
Tweeter Magnet	Neodymium
Transducer Impedence	LF 4ohm rated, HF 8ohm rated
Max SPL	125dB @1m/4Pi
Freq Range -10	52Hz - 20kHz
Freq Range -3	65Hz - 20kHz
Hor Dispersion	110°
Vert Dispersion	60°
Power Rating	1300W peak / 650 RMS
<b>AC Power Input</b>	100V-120V or 220V-240V
Cooling	Passive

LED Indicators	1 Power LED, 1 Limit LED, 1 Front LED, 2 Signal/SSM LEDs
Input Impedence	50k/100k un-balanced/balanced
Input Gain	-∞ to +36db
Crossover Freq	2 kHz
1/0	2 XLR Combo Jacks / BT
	1 XLR M Thru
Cabinet	PP+10% Talc
	1004
Grille	16GA perforated steel with acoustically transparent black cloth backing
Grille Suspension/ Mount	
Suspension/	black cloth backing 4 M10 Suspension points, 36mm Pole Socket, universal
Suspension/ Mount	black cloth backing  4 M10 Suspension points, 36mm Pole Socket, universal yoke bracket holes
Suspension/ Mount Handles	black cloth backing  4 M10 Suspension points, 36mm Pole Socket, universal yoke bracket holes  1, Cable channel on bottom
Suspension/ Mount Handles Net Weight	black cloth backing  4 M10 Suspension points, 36mm Pole Socket, universal yoke bracket holes  1, Cable channel on bottom  12 kg (26.46 lbs.)

## **EON710**




## 10-inch Powered PA Speaker with Bluetooth

### **SPEC SHEET**

### **FREQUENCY RESPONSE** ■





#### **PRODUCT DIMENSIONS** ■





HARMAN Professional 8500 Balboa Blvd. Northridge, CA 91329 USA

www.jblpro.com